

Safety Data sheet (SDS)

Revision Date: 2018/10/10

NO. OHPA_2025

Name: Antkote® 2025

Version: 01

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: Antkote® 2025

Additional Name: Hydroxyfunctional polyacrylic dispersion

Company Name: Wanhua Chemical Group Co., LTD

Address: No.17, Tianshan Rd, YEDA, Yantai, 264006, China

Emergencies Telephone: WANHUA +86 535-8203123 China +86 532-83889090

EU +31 20 20 65132/65130 \ +44 780 183 7343

NA 800-424-9300、+1-703-527-3887

Recommended uses:

It can be used for waterborne two-component coatings in combination with polyisocyanates or other crosslinkers ,or waterborne one component baking coatings in combination with amino resins or blocked polyisocyanates.

Section 2 - HAZARDS IDENTIFICATION

GHS Classification of the substance or mixture

Skin Corrosion/Irritation Category 3

Label elements

Pictogram : Not Applicable Signal words: WARNING

Hazard statements:

H316 Causes mild skin irritation.

Precautionary statements:

Preventive measures:

Use the necessary personal protective equipment (gloves, goggles, protective clothing etc.). Clean the exposed parts of the body in case of skin contact. No eating, drinking or smoking in the workplace. Use only outdoors or in a well-ventilated area.

Accident response:

If inhaled: In case of reactions, seek medical advice.

In case of eye or skin contact: Wash with plenty of water/soap. In case of reactions, consult a physician.

If swallowed: Rinse mouth. Do not induce vomiting. If swallowed seek medical advice immediately.

In case of leakage: Collect leakage.

Suitable extinguishing substances: Carbon dioxide (CO₂), Foam, Extinguishing powder, Water spray jet.

Storage:

Please store the product in sealed original packaging, cool and dry condition. Storage

temperature should be maintained between 5°C and 35°C. The product should be protected from freezing during storage. Immediately seal the package after use.

Disposal:

In order to avoid the damage to human body and environment, do not store food and other items in the used empty packaging without harmless treatment; Recycling, utilization and disposal packaging should be in accordance with the applicable legislation. The disposer should be response for the damage and loss caused by improper waste disposal.

Physical and chemical hazards: May cause pollution to water and soil.

Health hazard: No

Substance/mixture:

Environmental hazards: no release of dangerous substances. Do not allow to enter sewage system in case of blockage due to polymer deposition.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Mixture

Oubstance/inixture:		
Ingredient	Concentration	CAS No.
Polyacrylate containing	42-44%	N/A
hydroxylgroups	12 1170	IV/A
1-Butoxy-2-propanol	3.5%	5131-66-8
Butyl diglycol	3.5%	112-34-5

49-51%

7732-18-5

Version: 01

There is no GHS hazards classification for Polyacrylate containing hydroxylgroups The following substances are precautionary mentioned.

Neutralizing agent, bound as a salt:

Water

2-dimethylaminoethanol Concentration [wt-%]: < 2%

CAS-No.: 108-01-0 Index-No.: 603-047-00-0 EC-No.: 203-542-8

Classification (1272/2008/EC): Flam. Liq. 3 H226; Acute Tox.4 Inhalative H332; Acute Tox.4 Dermal H312; Acute Tox.4 Oral H302; Skin Corr. 1B H314; Eye Dam. 1 H318; STOT SE 3 H335

Specific threshold concentration (GHS): STOT SE 3 H335 >=5%

Section 4 - FIRST AID MEASURES

Description of first aid measures

General advice: In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

If inhaled: No special measures are necessary. In case of irritation, seek medical advice. In case of skin contact: Wash with plenty of water/soap. In case of skin reactions, consult a physician.

In case of eye contact: Rinse cautiously with water for at least 20 minutes. Tilt the head in order to avoid contact with the other eye. Contact an ophthalmologist.

If swallowed: In all cases of doubt, or when symptoms persist, seek medical advice immediately.

Revision Date: 2018/10/10

Most important symptoms and effects, both acute and delayed

Symptoms: May cause irritation by skin contact.

Indication of any immediate medical attention and special treatment needed

Immediate medical attention: First Aid, decontamination, treatment of symptoms.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Carbon dioxide (CO₂), Foam, Extinguishing powder, Water spray jet

In case of major fire and large quantities: Water spray jet, alcohol resistant foam Co-ordinate fire-fighting measures to the fire surroundings.

Advice for firefighters

Firefighters have to wear self-contained breathing apparatus.

Hazards during fire-fighting

Carbon monoxide, Carbon dioxide, Oxynitride.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protection equipment. Keep unauthorized persons away.

Environmental precautions

Do not empty into drains.

Methods and material for containment and cleaning up

Methods for cleaning up: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as described in the section on waste disposal.

Reference to other sections

Reference to other sections Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

Section 7 - HANDLING AND STORAGE

Control parameters

The product does not contain any relevant quantities of materials with critical values that have to be mentioned at the workplace.

Handling

The precautions required in the handling of solvents must be taken. Ensure adequate ventilation and, if necessary, exhaust ventilation when handling or transferring the product. Explosion protection required.

Storage

The product will keep stable for 6 months when stored in its sealed original packaging at temperatures between 5°C and 35°C. Storage at temperatures below 5°C will make the product frozen and cause irreversible damage. The product should therefore be protected from freezing during storage. Temperatures higher than 35°C should be avoided in order

Version: 01

Revision Date: 2018/10/10

to prevent the evaporation of water, which will result in the formation of a non-redispersible polymer film.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure controls

Respiratory protection: Respiratory equipment required in insufficiently ventilated working areas and during spraying.

Hand protection: Suitable materials for safety gloves; EN 374: Butyl rubber – IIR: thickness >=0.5mm; breakthrough time >=480min.

Recommendation: contaminated gloves should be disposed of.

Conditionally suitable materials for protective gloves; EN 374:

Nitrile rubber - NBR (>=0.35mm)

Breakthrough time not tested; dispose of immediately after contamination.

Eye protection: Wear eye/face protection.

Body protection: Wear suitable protective clothing.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Status liquid Appearance Milky white Water Solubility Misible Odour Slight inherent odour Flammability No Vapour pressure (kPa) Not established pH 7.0-9.0 Partition coefficient n-octanol / water (logkow) Flash point (°C) >93 Density (g/cm3) 1.05 at 20 °C Upper Explosive Limit[%(v/v)] Not applicable Lower Explosive Limit[%(v/v)] Not applicable Boiling point (°C) Not established Explosive properties Not applicable Auto-ignition temperature (°C) Not applicable Oxidising properties Not applicable Undersupposition temperature Not established Decomposition temperature Not established Volatile substance Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Not established Vapour density (Air = 1) Not established Relative density (Water = 1) 1.05 Viscosity, dynamic 500 – 4000 mPa.s at 25 °C VOC (g/l) Not established			
Water Solubility Misible Odour Slight inherent odour Flammability No Vapour pressure (kPa) Not established PH 7.0-9.0 Partition coefficient n-octanol / water (logkow) Flash point (°C) Jensity (g/cm3) Los at 20 °C Upper Explosive Limit[%(v/v)] Not applicable Lower Explosive Limit[%(v/v)] Boiling point (°C) Not established Explosive properties Not applicable Auto-ignition temperature (°C) Decomposition temperature Not established Oxidising properties Not applicable 1-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Not established Vapour density (Air = 1) Not established Relative density (Water = 11) Viscosity, dynamic Slight inherent odour Not established Not established Putyl diglycol, 2-dimethylaminoethanol Not established Not established Vapour density (Water = 1) Viscosity, dynamic Slight inherent odour Not established Not established Putyl diglycol, 2-dimethylaminoethanol Not established Not established	Status	liquid	
Odour Slight inherent odour Flammability No Vapour pressure (kPa) Not established pH 7.0-9.0 Partition coefficient n-octanol / water (logkow) Flash point (°C) >93 Density (g/cm3) 1.05 at 20 °C Upper Explosive Limit[%(v/v)] Not applicable Lower Explosive Limit[%(v/v)] Not applicable Boiling point (°C) Not established Explosive properties Not applicable Auto-ignition temperature (°C) Not applicable Decomposition temperature Oxidising properties Not applicable Volatile substance 1-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Not established Vapour density (Air = 1) Not established Relative density (Water = 1) 1.05 Viscosity, dynamic 500 – 4000 mPa.s at 25 °C	Appearance	Milky white	
Flammability Vapour pressure (kPa) Not established PH 7.0-9.0 Partition coefficient n-octanol / water (logkow) Flash point (°C) Pensity (g/cm3) 1.05 at 20 °C Upper Explosive Limit[%(v/v)] Lower Explosive Limit[%(v/v)] Boiling point (°C) Xot applicable Explosive properties Not applicable Auto-ignition temperature (°C) Decomposition temperature Oxidising properties Not applicable 1-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Vapour density (Air = 1) Not established Viscosity, dynamic Not established Vood mPa.s at 25 °C	Water Solubility	Misible	
Vapour pressure (kPa) Not established pH 7.0-9.0 Partition coefficient n-octanol / water (logkow) Not established Flash point (℃) >93 Density (g/cm3) 1.05 at 20 ℃ Upper Explosive Limit[%(v/v)] Not applicable Lower Explosive Limit[%(v/v)] Not applicable Boiling point (℃) Not established Explosive properties Not applicable Auto-ignition temperature (℃) Not applicable Decomposition temperature Not established Oxidising properties Not applicable I −Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Not established Vapour density (Air = 1) Not established Relative density (Water = 1) 1.05 Viscosity, dynamic 500 – 4000 mPa.s at 25 ℃	Odour	Slight inherent odour	
Partition coefficient n-octanol / water (logkow) Flash point (°C) Density (g/cm3) Loyer Explosive Limit[%(v/v)] Boiling point (°C) Not applicable Explosive properties Not applicable Auto-ignition temperature Oxidising properties Not applicable Decomposition temperature Not established Oxidising properties Not applicable Not applicable Decimposition temperature Not established Oxidising properties Not applicable I - Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Not established Vapour density (Air = 1) Relative density (Water = 1) Viscosity, dynamic Not established 7.0-9.0 Not applicable Not applicable 1 - Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Not established	Flammability	No	
Partition coefficient n-octanol / water (logkow) Flash point (°C) Density (g/cm3) Loyer Explosive Limit[%(v/v)] Lower Explosive Limit[%(v/v)] Boiling point (°C) Explosive properties Not applicable Auto-ignition temperature (°C) Decomposition temperature Oxidising properties Not applicable Not applicable Not applicable Decomposition temperature Not established Oxidising properties Not applicable I - Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Not established Vapour density (Air = 1) Relative density (Water = 1) Viscosity, dynamic Not established Not established Not established Not established	Vapour pressure (kPa)	Not established	
n-octanol / water (logkow) Flash point (°C) >93 Density (g/cm3) 1.05 at 20 °C Upper Explosive Limit[%(v/v)] Not applicable Lower Explosive Limit[%(v/v)] Not applicable Boiling point (°C) Not established Explosive properties Not applicable Auto-ignition temperature (°C) Not applicable Oxidising properties Not applicable Oxidising properties Not applicable Under the perature Not established Not applicable I − Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Not established Vapour density (Air = 1) Not established Relative density (Water = 1) Viscosity, dynamic 500 − 4000 mPa.s at 25 °C	pH	7.0-9.0	
n-octanol / water (logkow) Flash point (°C) >93 Density (g/cm3) 1.05 at 20 °C Upper Explosive Limit[%(√√)] Not applicable Lower Explosive Limit[%(√√)] Not applicable Boiling point (°C) Not established Explosive properties Not applicable Auto-ignition temperature (°C) Not applicable Decomposition temperature Oxidising properties Not applicable Volatile substance 1-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Not established Vapour density (Air = 1) Not established Relative density (Water = 1) 1.05 Viscosity, dynamic 500 - 4000 mPa.s at 25 °C	Partition coefficient	Niett-bilebi-d	
Density (g/cm3) Upper Explosive Limit[%(\(\psi\nu)\)] Lower Explosive Limit[\(\psi\nu\nu)\)] Not applicable Boiling point (\(^\mathbb{C}\)) Explosive properties Not applicable Auto-ignition temperature (\(^\mathbb{C}\)) Decomposition temperature Not established Oxidising properties Not applicable 1-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Not established Vapour density (Air = 1) Not established Relative density (Water = 1) Viscosity, dynamic 1.05 Not applicable 1-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Not established	n-octanol / water (logkow)	Not established	
Upper Explosive Limit[%(v/v)] Not applicable Lower Explosive Limit[%(v/v)] Not applicable Boiling point (°C) Not established Explosive properties Not applicable Auto-ignition temperature (°C) Not applicable Decomposition temperature Not established Oxidising properties Not applicable 1-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Not established Vapour density (Air = 1) Not established Relative density (Water = 1) 1.05 Viscosity, dynamic 500 - 4000 mPa.s at 25 °C	Flash point (℃)	>93	
Lower Explosive Limit[%(v/v)] Not applicable Boiling point (°C) Not established Explosive properties Not applicable Auto-ignition temperature (°C) Not applicable Decomposition temperature Oxidising properties Not applicable Under Composition temperature Oxidising properties Not applicable 1-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Not established Vapour density (Air = 1) Not established Relative density (Water = 1) Viscosity, dynamic 500 – 4000 mPa.s at 25 °C	Density (g/cm3)	1.05 at 20 ℃	
Boiling point (°C) Not established Explosive properties Not applicable Auto-ignition temperature (°C) Not applicable Decomposition temperature Not established Oxidising properties Not applicable I=Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Not established Vapour density (Air = 1) Not established Relative density (Water = 1) 1.05 Viscosity, dynamic 500 – 4000 mPa.s at 25 °C	Upper Explosive Limit[%(v/v)]	Not applicable	
Explosive properties Auto-ignition temperature (°C) Decomposition temperature Not established Oxidising properties Not applicable 1-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Vapour density (Air = 1) Relative density (Water = 1) Viscosity, dynamic Not applicable 1-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Not established Vapour density (Air = 1) Not established 7-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Not established	Lower Explosive Limit[%(v/v)]	Not applicable	
Auto-ignition temperature (°C) Not applicable Decomposition temperature Not established Oxidising properties Not applicable 1-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Not established Vapour density (Air = 1) Not established Relative density (Water = 1) 1.05 Viscosity, dynamic 500 – 4000 mPa.s at 25 °C	Boiling point (°C)	Not established	
Decomposition temperature Oxidising properties Not applicable 1-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Vapour density (Air = 1) Relative density (Water = 1) Viscosity, dynamic Not established 500 - 4000 mPa.s at 25 °C	Explosive properties	Not applicable	
Oxidising properties Not applicable 1-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Vapour density (Air = 1) Relative density (Water = 1) Viscosity, dynamic Not applicable 1-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Not established Not established 1.05	Auto-ignition temperature (°C)	Not applicable	
Volatile substance 1-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Vapour density (Air = 1) Relative density (Water = 1) Viscosity, dynamic 1-Butoxy-2-propanol, Butyl diglycol, 2-dimethylaminoethanol Not established Not established 500 – 4000 mPa.s at 25 °C	Decomposition temperature	Not established	
Volatile substance Butyl diglycol, 2-dimethylaminoethanol Molecular weight(g/mol) Not established Vapour density (Air = 1) Not established Relative density (Water = 1) 1.05 Viscosity, dynamic 500 − 4000 mPa.s at 25 °C	Oxidising properties	Not applicable	
2-dimethylaminoethanol Molecular weight(g/mol) Vapour density (Air = 1) Relative density (Water = 1) Viscosity, dynamic 2-dimethylaminoethanol Not established 1.05 500 – 4000 mPa.s at 25 °C		1-Butoxy-2-propanol,	
Molecular weight(g/mol) Not established Vapour density (Air = 1) Not established Relative density (Water = 1) 1.05 Viscosity, dynamic 500 − 4000 mPa.s at 25 °C	Volatile substance	Butyl diglycol,	
Vapour density (Air = 1) Relative density (Water = 1) Viscosity, dynamic Not established 1.05 500 – 4000 mPa.s at 25 °C		2-dimethylaminoethanol	
Relative density (Water = 1) 1.05 Viscosity, dynamic 500 – 4000 mPa.s at 25 °C	Molecular weight(g/mol)	Not established	
Viscosity, dynamic 500 − 4000 mPa.s at 25 °C	Vapour density (Air = 1)	Not established	
	Relative density (Water = 1)	1.05	
VOC (g/l) Not established	Viscosity, dynamic	500 − 4000 mPa.s at 25 °C	
	VOC (g/l)	Not established	

9.2 Other information

The indicated values do not necessarily correspond to the product specification. Please refer to the technical information sheet for specification data.

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

10.1 Stability

No decomposition when used and stored properly.

10.2 Materials to avoid

Acids, bases and electrolyte solution.

10.3 Conditions to avoid

Strong light, high temperature and low temperature.

10.4 Hazadous decomposition products

On drying of the coating release of neutralizing agent.

Section 11 - TOXICOLOGICAL INFORMATION

Toxicological studies on the product are not yet available.

Polyacrylate containing hydroxylgroups:

TOXICITY:

Not available

IRRITATION:

Not available

1-Butoxy-2-propanol:

TOXICITY:

dermal (rat) LD50: >2000 mg/kg[1]

Inhalation (rat) LC50: >1997.718 mg/l/8hE

Oral (rat) LD50: >2000 mg/kg

IRRITATION: Eye (rabbit): Not Available

Butyl diglycol:

TOXICITY:

dermal (rat) LD50: >2000 mg/kg Oral (rat) LD50: =4500 mg/kg

IRRITATION: Eye (rabbit): Not Available

Section 12 - ECOLOGICAL INFORMATION

Toxicity:

		TEST			
	ENDPOINT	DURATION	SPECIES	VALUE	SOURCE
		(HR)			
A1	NI - 4 A : I - I - I -	Not Available Not Available	Not	Not	
Antkote® 2025 NotAvailab	Not Available		Not Available	Available	Available
Polyacrylate containing hydroxylgroups	Not Available	Not Available	Not Available	Not Available	Not Available
1-Butoxy-2-propanol	Not Available	Not Available	Not Available	Not Available	Not Available

	LC50	96	Fish	1300mg/L	4
	EC50	48	Crustacea	>100mg/L	1
Butyl diglycol	EC50	96	Algae or other aquatic plants	>100mg/L	1
	NOEC	96	Algae or other aquatic plants	>=100mg/L	1

Persistence and degradability:

<u> </u>		
Ingredient	Persistence: Water/Soil	Persistence: Air
1-Butoxy-2-propanol	Low	Low
Butyl diglycol	Low	Low
Water	Low	Low

Bioaccumulative potential:

Ingredient	Bioaccumulation
1-Butoxy-2-propanol	LOW (LogKOW = 0.9842)
Butyl diglycol	LOW (BCF = 0.46)
Water	LOW (LogKOW = -1.38)

Mobility in soil:

Ingredient	Mobility
1-Butoxy-2-propanol	HIGH (KOC = 1.289)
Butyl diglycol	LOW (KOC = 10)
Water	LOW (KOC = 14.3)

Section 13 - DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal considerations: Do not dispose of with household waste. Do not allow to enter drains. Dispose of waste according to applicable legislation.

Uncleaned empty packaging: Handle contaminated packages in the same way as the substance itself.

Suitable cleaning agents: Water (with cleaning agent). Retain contaminated washing water and dispose it.

Section 14 - TRANSPORTATION INFORMATION

ADR/RID

14.1 UN number Not dangerous goods

14.2 UN proper shipping name Not dangerous goods

14.3 Transport hazard class Not dangerous goods

Not dangerous goods
Not dangerous goods
Not dangerous goods
Not dangerous goods
Not dangerous goods

14.6 Special precautions for user

See section 6-8.

Additional information : Not dangerous cargo.

Avoid heat above 35°C or lower than 5°C, stay away from food, acids and bases. According to the lastest

IATA DGR, this product is not dangerous.

Section 15 - REGULATORY INFORMATION

15.1 The product is classified and labeled according to Regulation (EC)No. 1272/2008

(GHS/CLP).

15.2 Safety, health and environmental regulation/legislation specific for the substance or mixture Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances.

Not applicable

Section 16 - OTHER INFORMATION

Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guideline for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.