

Water Dispersible Polyisocyanate

## Technical Data Sheet

Name: Aquolin<sup>®</sup> 269  
Revision Date: 2018-11-01

NO. WHSM\_269  
Version: 1.0

### Product Description

Aquolin<sup>®</sup> 269 is a water dispersible polyisocyanate based on hexamethylene diisocyanate (HDI). In combination with waterborne polyurethane, polyacrylate, etc., it can be used for water-borne coatings and adhesives. After addition of Aquolin<sup>®</sup> 269, the ready-to-use mixture must be used within the pot life.

### Properties

1. High gloss and high building up.
2. Excellent water resistance.
3. Excellent water dispersible and hand-mixing.
4. Excellent weather resistance.

### Characteristic data\*

Property	Value	Unit	Method
Appearance	Transparent to slightly yellowish liquid		
NCO content	18.8-19.8	%	GB/T 12009.4-2016
Viscosity	500-2000	mPa·s	Brookfield, LV, 63#, 30rpm, 25°C
Color APHA	< 80		GB/T 1722-1992
Monomeric isocyanate	≤ 0.2	%	GB/T 18446-2009
Flash point	~128	°C	GB/T 5208
Density	~1.13	g/cm <sup>3</sup>	GB/T 4472-2011

\*These properties are typical but do not constitute specifications.

### Storage

The product should be stored in dry conditions above 5°C and below 35°C with the integrity of the packaging, and prevent direct sunlight. The validity of this product is for 12 months, performance assessment is recommended before use after shelf life. The

# Aquolin<sup>®</sup> 269



product should be protected from freezing during storage. Water dispersible polyisocyanates are very moisture-sensitive and react with water to form carbon dioxide and insoluble ureas. The generation of carbon dioxide can lead to dangerous increases in pressure. The containers must always be kept tightly closed and the access of water in all forms must be prevented. It is suggested to use up once the package is open.

**Disclaimer:** Wanhua Chemical Group Co., LTD. recommends that any customers of this material should check with Materials Safety Data Sheet (MSDS) for details about safely handling this material. We also suggest that you contact the suppliers of any other materials used in our recommended formulations and suggestions for appropriate health and safety regulations prior to use. The information contained herein is believed to be reliable. However, nothing in this technical sheet should be considered as a representation of warranty, express or implicit, regarding the product characteristics, application, quality, safety, merchantability or fitness for a particular purpose. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.

**This is a trial product. Further information may be compiled in the future. Commercialization and continued supply of this material are not assured.**